


PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : C01B 3/58, B01J 19/24, 8/04	A1	(11) International Publication Number: WO 00/32513 (43) International Publication Date: 8 June 2000 (08.06.00)
(21) International Application Number: PCT/GB99/03958 (22) International Filing Date: 29 November 1999 (29.11.99) (30) Priority Data: 9826222.3 1 December 1998 (01.12.98) GB (71) Applicant (for all designated States except US): JOHNSON MATTHEY PUBLIC LIMITED COMPANY [GB/GB]; 2-4 Cockspur Street, Trafalgar Square, London SW1Y 5BQ (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): GRAY, Peter, Geoffrey [AU/GB]; The Linney, Blounts Court Road, Sonning Common, Reading RG4 9RS (GB). PIGNON, John, Frederick [GB/GB]; 14 Castle Close, Benson, Oxon OX10 6SN (GB). (74) Agent: WISHART, Ian, Carmichael; Johnson Matthey Technology Centre, Blounts Court, Sonning Common, Reading RG4 9NH (GB).		(81) Designated States: CA, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>
(54) Title: REACTOR AND PROCESS FOR REMOVAL OF CARBON MONOXIDE FROM HYDROGEN  <p>The diagram shows a cross-section of a reactor vessel (1) with a central horizontal tube. Above the tube, there are three sets of gas mixing means labeled 9a, 9b, and 9c. Below the tube, there are four sets of cooling coils labeled 4, 4, 4, and 4. A compact reformer (3) is shown on the right side of the vessel. A flow line with a pump (6) and a valve (7) is shown at the bottom. The vessel has an inlet (2) on the left and an outlet (5) on the right. A second inlet (8) is also shown on the left side.</p>		
(57) Abstract A reactor vessel (1) contains one or more selective oxidation stages and has counter-current cooling (5, 6, 7), each stage having an inlet for feedstock such as CO-contaminated hydrogen (2), an inlet for a second feedstock such as oxygen or air (8), gas mixing means (9a, 9b) and a catalytic reaction zone (4), preferably containing a metal support carrying a selective oxidation catalyst. A compact reformer with a very low pressure drop is suitable for producing hydrogen for fuel cell.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

REACTOR AND PROCESS FOR REMOVAL OF CARBON MONOXIDE FROM HYDROGEN

5

The present invention concerns an improved reactor, more particularly it concerns a reactor particularly adapted for and suitable for certain selective oxidation reactions.

We have previously developed certain selective oxidation processes for the removal
10 of residual carbon monoxide in hydrogen-containing gases intended as feedstock for fuel cells. Such processes are disclosed and claimed in for example, PCT/GB98/02873. It has become well established that hydrogen-fuelled fuel cells require very low proportions of carbon monoxide, which acts as a catalyst poison and degrades performance of the fuel cell. Desirably, the amount of CO is less than 10 ppm. If a liquid fuel is reformed to form a
15 hydrogen-containing fuel, levels of CO are produced which may vary about 0.5-5mol%, so that it becomes necessary to attenuate such CO levels. As mentioned in the above International Application, catalytic selective oxidation reactions are highly exothermic with the result that increasing reaction temperatures lead to increasing loss of valuable hydrogen due to competing reactions.

20

There remains a need for a catalytic selective oxidation reactor which permits good temperature control yet is simple, effective and inexpensive to manufacture. Although hydrogen "cleaned-up" by the reactor of the present invention may be used as fuel cell fuel, there are many other uses for such hydrogen. Also, although the reactor is particularly
-25 suitable for the cleaning up of reformat (which may be from methanol, other oxygenated fuels, gasoline or other hydrocarbon fuels), it is not limited to such use. Accordingly, the present invention provides a reactor for catalytic selective oxidation, comprising a reactor vessel with counter current cooling and at least one stage, each stage provided with an inlet for a first feedstock, e.g. CO contaminated hydrogen, an inlet for a second feedstock,
30 e.g. oxygen-containing gas, gas mixing means and a catalytic reaction zone, preferably comprising a selective oxidation catalyst deposited on a substrate having good heat conduction properties.

The invention also provides a process for the removal of quantities of CO from a
35 hydrogen feedstock by partial oxidation, comprising at least one step of admixing said

feedstock with a quantity of oxygen, passing the resulting mixture over a selective oxidation catalyst in a selective oxidation zone and recovering a hydrogen product with reduced content of CO, whilst simultaneously cooling the selective oxidation zone, preferably to maintain the selective oxidation zone at a temperature in the range 100 to 250°C, by counter-current coolant flow.

The reactor, in its most preferred embodiment, has four stages and this is effective to reduce a reformat having a CO content of 1 to 2% to below 10ppm. In other embodiments, there may be 2 to 10 stages.

10

The reactor is suitably in the form of a vessel in which the reaction zones are generally annular in shape, and provided with internal and/or external liquid cooling. Cooling is preferably provided by internal cooling using water, which is suitably under pressure to prevent boiling at the temperatures generated. Other liquid coolants, or forced air cooling may be used if desired. According to specific reactor designs, heat removal may be enhanced by increasing heat exchange surface areas by corrugation or other established means. Heat removal may be altered by altering the flow of coolant and/or altering the quantity of heat removed from the coolant by means of a heat exchanger.

20

Each reaction zone suitably comprises a metallic catalyst support ("monolith") of generally honeycomb construction, as is in common use in automobile exhaust gas catalysis. These may have 50 to 1200 cells per square in cell density, preferably 200 to 600 cpsi, and may be of a variety of types of stainless steel. In general, the present invention does not result in the reaction stages reaching the higher temperatures generally met with in exhaust gas catalysis (e.g. 500-900°C), but the material should be capable of resisting temperature excursions. An alternative reaction zone design utilises what has become known as "static mixers" which combine a very high degree of gas agitation and mixing, resulting in non-laminar flow, with relatively low pressure drop. Such static mixers may be manufactured from a variety of metals and are commercially available. However, it is presently preferred to use a honeycomb monolith.

30

The reaction zone desirably carries a selective oxidation catalyst comprising a platinum group metal, especially comprising platinum and/or rhodium, carried on a high

surface area metal oxide support, such as alumina. The metallic catalyst support may be coated by generally known methods with a slurry of oxide support, dried and fired, and then impregnated with the catalytically active components, before a final firing. Such procedures are in themselves known, and do not form part of this invention.

5

The invention will now be described with reference to the accompanying drawing which shows a cross-section of one embodiment of the present invention.

An essentially cylindrical metal vessel, made by pressing two halves and
10 seam-welding, has a main gas inlet, 2, for reformat gas, and an outlet, 3, for cleaned gas. The vessel has a number of annular reaction zones, 4, each consisting of an annular wound corrugated catalyst support. The vessel further has an internal water jacket, 5, between a spacer and the shell and this is supplied with cooling water by means of a water circuit comprising a circulating pump, 6, and a heat exchanger, 7. The heat exchanger is desirably
15 used to recover heat in an integrated system e.g. in an integrated combined heat and power system. The vessel further is provided with four air inlets, 8, each providing pre-determined (for a steady-state operation) levels of air (that is reaction oxygen; air is generally suitable). Although not preferred, controlled amounts of oxygen, according to one or more feedback or feed forward controls detecting gas flow levels and CO levels may be used. Downstream
20 of each air inlet is a gas mixing zone, 9a, 9b, 9c and 9d. Zone 9a is suitably a static mixer, but zones 9b, 9c and 9d are preferably alternating annular mixing vanes, 10, and discs, 11, having gas flow holes, as illustrated in Figs 2 and 3. It should be noted that for simplicity only four vanes and four holes are shown, but more, e.g. six or eight, may be used. Such vanes and discs may be manufactured by pressing to form a sleeve which may be fitted and
25 brazed or welded onto the jacket 5 with the intention that each gas mixing zone also serves to remove heat from the reaction gases leaving each reaction zone. Although the schematic drawing of the reactor shows each reaction zone and gas mixing zone of the same size, these may be designed to differ according to the amount of heat to be removed. Additionally, each reaction zone may incorporate different and/or different loadings, of catalyst. Each metal
30 catalyst support monolith suitably has 300-400 cells per sq.in. and is coated with a washcoat comprising ~36wt% alumina solids of D50 of approx 5µm and D90 of approx 16µm, to deposit approx 3g/m³. After drying and firing, the coated monolith was impregnated with

a platinum salt solution to result in 5% by wt of Pt deposited on the alumina. The resulting coated monolith was again dried and fired before being assembled into the reactor.

Initial studies indicate that a reformat containing 1-2% CO in admixture with H₂,
5 CO₂, N₂, water vapour with a small proportion of unreacted reformer feedstock (e.g. CH₃OH, CH₄, gasoline), at 180°C may be converted to a feed gas suitable for a fuel cell, containing below 10ppm CO, and at 140°C.

The reactor of the invention is compact and exhibits relatively low pressure drop.
10 Manufacturing costs are relatively low. The reactor is believed to be suitable for mobile or automobile uses as well as stationery uses. It is presently envisaged that the reactor shell will be lagged to control heat loss and prevent injury. The reactor can be manufactured simply and inexpensively, using pressed and welded parts. It is desirably operated to achieve low pressure drop, and the particular embodiment illustrated is designed for a gas
15 hourly space velocity of approx. 30,000h⁻¹ gas throughput.

The reactor as described may be altered in a variety of ways without departing from the central inventive concept.

20 The invention is now illustrated below in a working example of a two-stage reactor, fed with a synthetic reformat gas mixture containing N₂, H₂, CO, CO₂ and H₂O. Each of the two stages consists of a mixing zone with three off-set spiral vanes, followed by air injection accomplished through a number of apertures in an annular ring, producing a swirling, mixing gas. The thus mixed hydrogen and air mixture passes through an annular
25 metal honeycomb support mounted on a central cooling jacket. The cooling jacket is fed counter-current to the flow of hydrogen with a heat transfer fluid, conveniently water under pressure, and the metal honeycomb support is mounted in good heat exchange contact with the cooling jacket. The metal honeycomb carries a selective oxidation catalyst. Gas may be extracted for analysis between the two stages and/or after the second stage. By setting
30 the composition of the feedstock gas mixture according to that analysed after the first or second stage, the test two-stage reactor can model a three or four stage reactor.

The detailed operating conditions and other experimental detail for one typical run of the above reactor now follow. It was remarkable that the pressure drop across the whole of the est reactor was about the measurement limit of the gauges being used, and was of the order of 1.5-3mbar (150-300Pa), at the two throughputs tested. This indicates that the reactor is very efficient, compact and requires very little energy to operate.

1. Each catalyst support was an annular of internal diameter 3.85in (9.78cm), external diameter 5.85in (14.86cm) and 3.0in(7.62cm) length, made from "Fecralloy" steel and having 500 cells per sq in. Each support had been washcoated with alumina washcoat as used in exhaust gas catalytic convertors, followed by loading with 5% by wt of the alumina of Pt. Conventional manufacturing techniques were used.
2. The synthetic reformat had the compositions: 48%N₂(dry), 40%H₂ (dry), 10%CO₂(dry), 0.5-1.5%CO (dry) and 13% H₂O (of total flow). Two levels of CO concentration were chosen, a higher level to represent the output from autothermal reforming, and a lower level to represent the output from steam reformer or an optimised reformer, and two levels of throughput stated to be Nominal 3kWe (1kilowatt equivalent = 1,000 l/hr of H₂) and Nominal 6kWe, equal to 7,5000 l/hr of dry reformat and 15,000 l/hr of dry reformat respectively (8,620 l/hr and 17,240 l/hr of wet reformat).

It is plain from these results with a two-stage reformer that the compact and efficient reformer of the invention will be effective to remove CO from Hydrogen to any desired level, by conventional optimisation and especially by matching the number of stages to the requirements of the fuel cell system or other usage of the purified hydrogen.

TWO-STAGE ANNULAR SELOX REACTOR TEST RESULTS

FIRST STAGE							SECOND STAGE				
Ex No.	Power kW _e	CO in %, dry	Air in, slm	Temp in C	Temp out, C	CO out %, dry	Air in, slm	Temp in, C	Temp out, C	CO out ppm dry	Sel**
1	3	1.5	4	125	212	0.60	2	167	212	1610	0.696
2	3	1.5	4	127	214	0.60	3	167	217	740	0.640
3	3	1.5	4	125	210	0.60	4	169	227	950	0.556
4	3	1.5	3	125	149	0.81	3	129	175	1840	0.684
5	3	1.5	5	128	215	0.34	3	161	220	290	0.582
6	3	0.5	2	143	176	0.122	0.5	138	145	232	0.579
7	3	0.5	2	141	167	0.122	0.8	127	136	29	0.540
8	3	0.5	2	140	161	0.122	1.0	121	130	28	0.505
9	3	0.5	2	141	172	0.122	1.2	131	146	55	0.472
10	3	0.5	1.5	142	166	?	1.0	134	157	373	0.562
11	3	0.5	2.5	142	179	?	1.0	138	150	50	0.433
12	6	0.5	4	138	167	0.130	1	148	176	722	0.520
13	6	0.5	4	138	162	0.130	2	140	185	51	0.503
14	6	0.5	4	138	166	0.130	3	146	198	105	0.428
15	6	0.5	6	138	205	62ppm	0	176	174	62	0.502

** Sel: (Selectivity) = CO consumed/2 x O₂ consumed

CLAIMS

1. A catalytic selective oxidation reactor, comprising a reactor vessel (1) with converter
current cooling means (5,6,7) and at least one stage, each stage being provided with
5 an inlet for a first feedstock (2), and inlet for a second feedstock (8), gas mixing
means (9a) and a catalytic reaction zone (4).
2. A reactor according to claim 1, wherein the catalytic reaction zone comprises a
selective oxidation catalyst deposited upon a metal support.
- 10 3. A reactor according to claim 2, wherein the metal support is mounted in good heat
exchange contact with the cooling means.
4. A reactor according to any one of the preceding claims, wherein the cooling means
15 comprises a central jacket mounted within the reactor.
5. A reactor according to any one of the preceding claims, having from 2 to 10 stages.
6. A reactor according to claim 5, having four stages.
- 20 7. A reactor according to any one of the preceding claims, connected to the output from
a reformer such that CO is removed from the output gas to a level where the output
from the reactor may be fed to a fuel cell.
- 25 8. A process for the removal of quantities of CO from a hydrogen feedstock by partial
oxidation, comprising at least one step of admixing said feedstock with a quantity of
oxygen, passing the resulting mixture over a selective oxidation catalyst in a selective
oxidation zone and recovering a hydrogen product with reduced content of CO, whilst
simultaneously cooling the selective oxidation zone by counter-current coolant flow.
- 30 9. A process according to claim 8, wherein the selective oxidation zone is maintained
at a temperature in the range 100 to 250°C.

10. A process according to claim 8 or 9, providing hydrogen to fuel a fuel cell.





Fig 3




Fig 2

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/GB 99/03958

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 C01B3/58 B01J19/24 B01J8/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C01B B01J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 93 19005 A (INT FUEL CELLS CORP) 30 September 1993 (1993-09-30) page 9, line 2 -page 12, line 32 figure 1 ---	1,4,5, 7-10
X	DE 195 44 895 C (DAIMLER BENZ AG) 27 February 1997 (1997-02-27) column 2, line 23 - line 47 column 3, line 35 -column 4, line 50 ---	1-3,5-10
X	GB 2 075 859 A (HUMPHREYS & GLASGOW LTD) 25 November 1981 (1981-11-25) claims; figures ---	1,4-6
X	US 4 988 431 A (HEISEL, M ET AL.) 29 January 1991 (1991-01-29) claims; figure ---	1,4,5
-	--- -/-	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

A document member of the same patent family

Date of the actual completion of the international search

16 February 2000

Date of mailing of the international search report

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Van der Poel, W

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 99/03958

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 43 34 981 A (DAIMLER BENZ AG) 20 April 1995 (1995-04-20) the whole document ---	1,2,5-10
A	EP 0 305 203 A (TOPSOE HALDOR AS) 1 March 1989 (1989-03-01) page 3, line 37 - line 63 page 4, line 19 - line 21 page 4, line 51 - line 61 -----	

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/GB 99/03958

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9319005 A	30-09-1993	US 6010675 A DE 69325092 D DE 69325092 T EP 0631564 A EP 0873967 A US 5330727 A	04-01-2000 01-07-1999 30-09-1999 04-01-1995 28-10-1998 19-07-1994
DE 19544895 C	27-02-1997	EP 0776861 A US 5874051 A	04-06-1997 23-02-1999
GB 2075859 A	25-11-1981	NONE	
US 4988431 A	29-01-1991	DE 3631642 A CA 1295815 A DE 3775672 A EP 0260530 A US 5084247 A	07-04-1988 18-02-1992 13-02-1992 23-03-1988 28-01-1992
DE 4334981 A	20-04-1995	EP 0650923 A US 5674460 A	03-05-1995 07-10-1997
EP 0305203 A	01-03-1989	DK 448187 A CA 1304215 A DE 3885545 D DE 3885545 T JP 1139137 A JP 2592662 B NO 883826 A,B, US 4985230 A	28-02-1989 30-06-1992 16-12-1993 10-03-1994 31-05-1989 19-03-1997 28-02-1989 15-01-1991